



Features

REED R5008 Compact Digital Multimeter with Temperature

- Measures AC/DC voltage and current, frequency, resistance, capacitance and temperature
- Diode check and continuity functions
- Relative and data hold functions
- Double molded plastic housing
- Cat. III 600V safety rating

REED R2002 Compact Infrared Thermometer

- Built-in laser pointer identifies target area
- Compact size
- 8:1 distance to spot size ratio
- User selectable °F or °C
- Fixed emissivity covers 90% of applications
- Automatic data hold with on-screen min/max readings
- Backlit display
- Low battery indication and auto shut off

TECHNICAL DATA

REED R5100 Non-Contact AC Voltage Detector with Flashlight

- Suitable for outlets or against insulated wire
- Built-in flashlight
- Double insulated housing for increased safety
- Audible (buzzer) and visual (LED) indicators when voltage present
- For use on 50/60Hz circuits
- Pocket clip
- Auto shut off
- CE and UL approved
- Cat. III 1000V, Cat. IV 600V safety ratings

REED AD-1 Thermocouple Adapter

- For use with REED multimeters and clamp meters with contact temperature functionality. Measurement accuracy and temperature range are dependent upon probe.

REED TP-01 Beaded Thermocouple Wire Probe

- Measurement range: -40 to 482°F (-40 to 250°C)
- For general purpose temperature applications
- Fast response time
- Compatible with Type-K temperature measuring instruments
- 38" (96.5cm) wire length

REED R1000 Safety Test Lead Set, Double Insulated

- Sharp points for piercing insulation
- Stainless steel tips
- Ergonomic comfort grip
- 48" (1.2m) long
- 0.2" (5mm) tip length
- 6.1" (155mm) probe length
- 1000V, 10A
- CAT III. 1000V and CAT IV. 600V
- CE certified

REED R8888 Deluxe Carrying Case

- Customizable foam interior
- O-ring creates watertight seal
- Pressure equalization valve
- Double latch & lock system
- Internal dimensions: 12 x 9.6 x 5.4" (305 x 244 x 136mm)
- External dimensions: 13 x 12 x 5.8" (330 x 305 x 148mm)
- Weight: 4.55lbs (2.1kg)

Model	Description
RTEMP-KIT	Temperature Combination Kit