

Features

- Detects all CFCs, HFCs, and HCFCs
- Quick response and high accuracy detects small leaks
- 15" (390mm) gooseneck for hard to reach areas
- Designed for one-handed operation
- User adjustable sensitivity (High/Low)
- Tricolor visual indicator
- Audible (buzzer) and visual (LED) alarm indicators
- Low battery indicator and auto shut off
- User replaceable sensor
- Includes reference leak source, batteries and hard carrying case

Specifications

| | |
|-----------------|---|
| Detected Gases: | CFC's: R11, R12, R13 HCFC's: R22, R502, R500 HFC's: R134a, R123, R125, R23, R404A, R407C, R410A and other halogen based compounds |
| Sensitivity: | R22, 134A: 6g/year(H), 30g/year(L) R404A, 407C, 410A: 8g/year(H), 40g/year(L) |

General Specifications

| | |
|-------------------------|---|
| Sensor Type: | Advanced ionization detector |
| Display: | Tricolor LED bar indicator |
| Alarm: | Audible (buzzer) and Visual (bar indicator) |
| Sensitivity Settings: | Low and High |
| Warm-up Time: | 10 seconds |
| Response Time: | Less than 1 second |
| Auto Shut-off: | Yes (after 10 mins) |
| Low Battery Indicator: | Yes |
| Power Supply: | 4 AA Batteries |
| Battery Life: | Approx. 40 hours |
| Product Certifications: | CE, RoHS |
| Probe Length: | 15" (390mm) |
| Operating Temp.: | 32 to 104°F (0 to 40°C) |
| Storage Temp.: | 14 to 140°F (-10 to 60°C) |
| Operating Humidity: | 10-70% |
| Dimensions: | 8.5 x 2.6 x 2.2" (217 x 66 x 56mm) |
| Weight: | 9.3 oz (265g) |

TECHNICAL DATA



| Model | Description |
|------------|-----------------------------------|
| C-380 | Refrigerant Leak Detector |
| R-134A | Replacement Sensor |
| LC-R01 | Replacement Reference Leak Source |
| R8888 | Deluxe Hard Carrying Case |
| C-380-NIST | Refrigerant Leak Detector & NIST |