

TECHNICAL DATA

Specifications

AC/DC Voltage

Range: AC: 400mV, 4, 40, 400, 600V
DC: 400mV, 4, 40, 400, 600V

Accuracy: AC: 400mV $\pm(15\% \text{ rdg.} + 15 \text{ dgt.})$
4V $\pm(1.2\% \text{ rdg.} + 3 \text{ dgt.})$
40, 400V $\pm(1.5\% \text{ rdg.} + 3 \text{ dgt.})$
600V $\pm(2.0\% \text{ rdg.} + 4 \text{ dgt.})$
DC: 400mV $\pm(0.05\% \text{ rdg.} + 2 \text{ dgt.})$
4, 40, 400V $\pm(1.2\% \text{ rdg.} + 2 \text{ dgt.})$
600V $\pm(1.5\% \text{ rdg.} + 2 \text{ dgt.})$

Resolution: AC: 0.1mV, 1, 10, 100V
DC: 0.1mV, 1, 10, 100V

AC/DC Current

Range: 400, 4000 μ A, 40, 400mA, 10A

Accuracy: AC: 400 μ A $\pm(1.5\% \text{ rdg.} + 5 \text{ dgt.})$
4000 μ A/40, 400mA $\pm(1.8\% \text{ rdg.} + 5 \text{ dgt.})$
10A $\pm(3.0\% \text{ rdg.} + 7 \text{ dgt.})$
DC: 400 μ A $\pm(1.0\% \text{ rdg.} + 3 \text{ dgt.})$
4000 μ A/40, 400mA $\pm(1.5\% \text{ rdg.} + 3 \text{ dgt.})$
10A $\pm(2.5\% \text{ rdg.} + 5 \text{ dgt.})$

Resolution: 0.1, 1 μ A, 10, 100mA, 1A

Resistance

Range: 400 Ω , 4, 40, 400k Ω , 4, 40M Ω

Accuracy: 400 Ω : $\pm(1.2\% \text{ rdg.} + 4 \text{ dgt.})$
4k Ω : $\pm(1.0\% \text{ rdg.} + 2 \text{ dgt.})$
40, 400k Ω , 4M Ω : $\pm(1.2\% \text{ rdg.} + 2 \text{ dgt.})$
40M Ω : $\pm(2.0\% \text{ rdg.} + 3 \text{ dgt.})$

Resolution: 0.01 Ω , 1, 10, 100k Ω , 1, 10M Ω

Capacitance

Range: 4, 40, 400nF, 4, 40, 200 μ F

Accuracy: 4nF: $\pm(5.0\% \text{ rdg.} + 50 \text{ dgt.})$
40nF: $\pm(5.0\% \text{ rdg.} + 7 \text{ dgt.})$
400nF/4, 40 μ F: $\pm(3\% \text{ rdg.} + 5 \text{ dgt.})$
200 μ F: $\pm(5\% \text{ rdg.} + 5 \text{ dgt.})$

Resolution: 1, 10pF, 0.1, 1, 10nF, 0.1 μ F

Frequency

Range: 9.999, 99.99, 999.9Hz, 9.999, 99.99, 999.9KHz, 9.999MHz

Accuracy: 9.999, 99.99Hz: $\pm(1.5\% \text{ rdg.} + 5 \text{ dgt.})$
999.9Hz, 9.999, 99.99, 999.9KHz: $\pm(1.2\% \text{ rdg.} + 3 \text{ dgt.})$
9.999MHz: $\pm(1.5\% \text{ rdg.} + 4 \text{ dgt.})$

Resolution: 0.001, 0.01, 0.1, 1, 10, 100Hz, 1kHz

Temperature

Range: -4 to 1400°F (-20 to 760°C)

Accuracy: $\pm(3.0\% \text{ rdg.} + 9^\circ\text{F})$
 $\pm(3.0\% \text{ rdg.} + 5^\circ\text{C})$

Resolution: 1°F, 1°C

Continued...



Features

- Measures AC/DC voltage and current, frequency, resistance, capacitance and temperature
- Diode check and continuity functions
- Relative and data hold functions
- Double molded plastic housing
- Cat. III 600V safety rating
- Includes Thermocouple Adapter, thermocouple wire probe (Type K), test leads, battery and carrying case

TECHNICAL DATA



General Specifications

Range Selection:	Autoranging/Manual
Display:	4,000 count LCD display
Display Hold:	Yes
Peak Hold:	Yes
Relative Mode:	Yes
Diode Test:	Yes
Continuity Check:	Audible signal if resistance $\leq 150\Omega$
Duty Cycle:	Yes (0.1 - 99.9%)
Kick Stand:	Yes
Auto Power Off:	Yes (after 15 minutes)
Power Supply:	9V Battery
Low Battery Indicator:	Yes
Fuse Protection:	Yes
Replaceable Test Leads:	Yes
Overvoltage Category:	CAT. III 600V
Product Certifications:	CE
Operating Temperature:	32 to 122°F (0 to 50°C)
Storage Temperature:	-4 to 140°F (-20 to 60°C)
Dimensions:	5.9 x 2.8 x 1.9" (150 x 70 x 48mm)
Weight:	9oz (255g)

Model	Description
R5008	Multimeter with Temperature
FC-300	Fused Test Lead Set
P-15	Weatherproof Plug
CP-09	AC Current Adapter
AD-1	Thermocouple Adapter
TP-01	Type K Thermocouple Wire Probe
R1000	Safety Test Lead Set, Double Insulated
R2920	Surface Thermocouple Probe
R2930	Right Angle Thermocouple Surface Probe
R2950	Immersion Thermocouple Probe
CA-52A	Soft Carrying Case
R5008-NIST	Multimeter with Temperature & NIST