

TECHNICAL DATA

Features

- Measures AC/DC current/voltage, resistance, capacitance, frequency, duty cycle and temperature
- 50,000-count backlit LCD display with low battery and overrange indicators
- Built-in non-contact voltage detector with LED indicator
- True RMS AC measurements
- Display hold and relative mode
- Diode test and continuity check functions
- Durable double molded plastic housing
- Cat. III 600V safety rating
- Includes test leads, thermocouple wire probe, thermocouple adapter, batteries, and soft carrying case

Specifications

AC/DC Current

Range: 50, 500A
Accuracy: AC: $\pm(2.8\% \text{ rdg.} + 30 \text{ dgt.})$
DC: $\pm(2.5\% \text{ rdg.} + 30 \text{ dgt.})$
Resolution: 0.01, 0.1, 1A

AC/DC Voltage

Range: AC: 500mV, 5, 50, 500, 750V
DC: 500mV, 5, 50, 500, 1000V
Accuracy: AC: $\pm(1.0\% \text{ rdg.} + 30 \text{ dgt.})$
DC: $\pm(0.1\% \text{ rdg.} + 4 \text{ dgt.})$
Resolution: AC/DC: 0.1mV, 0.001, 0.01, 0.1, 1V

Resistance

Range: 500 Ω , 5, 50, 500k Ω , 5, 50M Ω
Accuracy: $\pm(1.0\% \text{ rdg.} + 4 \text{ dgt.})$
0.1 Ω , 0.001, 0.01, 0.1k Ω ,
0.001, 0.01M Ω

Capacitance

Range: 500, 5000nF, 50, 500 μ F, 5mF
Accuracy: $\pm(3.5\% \text{ rdg.} + 10 \text{ dgt.})$
Resolution: 0.01, 0.1nF, 0.01, 0.1 μ F, 0.1mF

Frequency

Range: 10kHz
Accuracy: $\pm(0.5\% \text{ rdg.} + 10 \text{ dgt.})$
Resolution: 0.001Hz



Continued...

Temperature

Range: -148 to 1832°F (-100 to 1000°C)
Accuracy: $\pm(1.0\% \text{ rdg.} + 4.5^\circ\text{F})$
 $\pm(1.0\% \text{ rdg.} + 2.5^\circ\text{C})$
Resolution: 1°F, 1°C

General Specifications

Range Selection: Autoranging / Manual
True RMS: Yes
Display: 50,000 count LCD display
Display Hold: Yes
Relative Mode: Yes
Diode Test: Yes
Backlit Display: Yes
Continuity Check: Audible signal if resistance $<35\Omega$
Duty Cycle: Yes
Non-Contact Voltage Detector: Yes
Autoshut off: Yes (after 15 mins)
Power Supply: 2 x AAA
Low Battery Indicator: Yes
Jaw Opening: 1.2" (30mm), up to 350 MCM
Overvoltage Category: CAT. III 600V
Product Certifications: CE
Operating Temperature: 32 to 122°F (0 to 50°C)
Storage Temperature: -4 to 140°F (-20 to 60°C)
Dimensions: 7.9 x 2.6 x 1.5"
(200 x 66 x 37 mm)
Weight: 8.1oz (230g)

TECHNICAL DATA



Model	Description
R5030	AC/DC Clamp Meter
AD-1	Thermocouple Adapter
R5400	Line Splitter
R1000	Safety Test Lead Set, Double Insulated
FC-300	Fused Test Lead Set
TP-01	Type K Thermocouple Wire Probe
R2920	Surface Thermocouple Probe
R2930	Right Angle Thermocouple Surface Probe
R2940	Air/Gas Thermocouple Probe
R2950	Immersion Thermocouple Probe
R2960	Needle Tip Thermocouple Probe
CA-52A	Soft Carrying Case
C-820	Soft Carrying Case
R5030-NIST	AC/DC Clamp Meter & NIST