

TECHNICAL DATA



Features

Model R2300 Infrared Thermometer

- Built-in laser pointer identifies target area
- User selectable °F or °C
- 12:1 distance to spot size ratio
- Digitally adjustable emissivity
- Max and Min readings
- Backlit display
- High and low alarms
- Low battery indication and auto shut off

Model C-380 Refrigerant Leak Detector

- Detects all CFCs, HFCs, and HCFCs
- Quick response and high accuracy detects small leaks
- 15" (390mm) gooseneck for hard to reach areas
- Designed for one-handed operation
- User adjustable sensitivity (High/Low)
- Tricolor visual indicator
- Audible (buzzer) and visual (LED) alarm indicators
- Low battery indicator and auto shut off
- User replaceable sensor

Model C-383 Combustible Gas Leak Detector

- Detects a wide range of combustible gases including: gasoline, propane, natural gas and fuel oil
- Quick response and high accuracy detects small leaks
- 15" (390mm) gooseneck for hard to reach areas
- Designed for one-handed operation
- Ambient concentration reset function
- User adjustable sensitivity (High/Low)
- Tricolor visual indicator
- Audible (buzzer) and visual (LED) alarm indicators
- Self test sequence on start-up
- Low battery indicator and auto shut off
- User replaceable sensor

Model R5100 Non-Contact AC Voltage Detector

- Suitable for outlets or against insulated wire
- Built-in flashlight
- Double insulated housing for increased safety
- Audible (buzzer) and visual (LED) indicators when voltage present
- For use on 50/60Hz circuits
- Pocket clip
- Auto shut off
- CE and UL approved
- Cat. III 1000V, Cat. IV 600V safety ratings

Model	Description
ST-HVACKIT2	HVAC Combo Kit