

TECHNICAL DATA



Features

- Compact design allows for one-handed operation
- Multi-angle measurement (20° / 60° / 85°)
- Backlit LCD display
- Auto calibration
- Internal memory stores last 254 data points
- Built-in rechargeable battery
- Designed to meet ASTM D523, ASTM D1455, ASTM C584 and ASTM D2457 international standards
- Includes ac adapter, calibration standard, cleaning cloth and hard carrying case

Specifications

| | |
|---------------------------|--------------------------------------|
| Measuring Range: | 0.1 to 200 GU |
| Measuring Geometry: | 20° / 60° / 85° |
| Accuracy: | ±1.0 GU |
| Resolution: | 0.1 GU |
| Repeatability: | ±0.5 GU |
| Measuring Area: | 7x14mm |
| Display: | LCD |
| Backlit Display: | Yes |
| Auto Shut-off: | Yes (after 30 mins) |
| Low Battery Indicator: | Yes |
| Power Supply: | Rechargeable Lithium Battery |
| Internal Memory: | Yes (up to 254 datapoints) |
| Product Certifications: | CE / RoHS |
| Operating Temperature: | 32 to 104°F (0 to 40°C) |
| Storage Temperature: | -4 to 140°F (-20 to 60°C) |
| Operating Humidity Range: | 0 to 85% |
| Dimensions: | 5.5 x 1.8 x 3" (140 x 45 x 75 mm) |
| Weight: | 10.76oz (305g) |

| Model | Description |
|-------|--------------------|
| R7700 | Gloss Meter |
| R8888 | Hard Carrying Case |